

What is claimed is:

1. A differential driver circuit comprising:  
an output driver circuit, including:  
differential amplifier circuitry;  
a first variable resistance circuit that is coupled to the differential amplifier circuitry; and  
a second variable resistance circuit that is coupled to the differential amplifier circuitry; and  
a feedback circuit that is coupled to the first and second variable resistance circuits, wherein a source resistance of the output driver circuit appears to a load as substantially similar to a termination resistance of the load.
2. The differential driver circuit of Claim 1, wherein  
the feedback circuit includes a scaled replica of a leg of the output driver circuit.
3. The differential driver circuit of Claim 1, wherein  
the feedback circuit is configured to adjust the first variable resistance circuit and the second variable resistance circuit to track a change in the termination resistance, such that the source resistance tracks the change in the termination resistance.
4. The differential driver circuit of Claim 1, wherein  
the differential amplifier circuitry includes:  
a first transistor that is coupled between the first variable resistance circuit and a first output node;  
a second transistor that is coupled between the first variable resistance circuit and a second output node;  
a third transistor that is coupled between the second variable resistance circuit and the first output node; and  
a fourth transistor that is coupled between the second variable resistance circuit and the second output node.

5. The differential driver circuit of Claim 1, wherein  
the first variable resistance circuit includes a transistor having a drain that is coupled to the differential amplifier circuitry and a gate that is coupled to the feedback circuit.
6. The differential driver circuit of Claim 5, wherein  
the feedback circuit is configured to adjust an on-resistance that is associated with the transistor.
7. The differential driver circuit of Claim 5, wherein  
the first variable resistance circuit further includes a resistor that is coupled in parallel with the transistor.
8. The differential driver circuit of Claim 5, wherein  
the second variable resistance circuit includes another transistor having a drain that is coupled to the differential amplifier circuitry and a gate that is coupled to the feedback circuit.
9. The differential driver circuit of Claim 8, wherein  
the feedback circuit is configured to modulate the transistor and the other transistor.
10. The apparatus of Claim 1, wherein  
the output driver circuit further includes a current source circuit that is coupled to the feedback circuit and the first variable resistance circuit.
11. The apparatus of Claim 10, wherein  
the output driver circuit further includes a current sink circuit that is coupled to the feedback circuit and the second variable resistance circuit.

12. The apparatus of Claim 1,  
wherein the feedback circuit includes a third variable resistance circuit,  
the third variable resistance circuit includes a replica of the first variable  
resistance circuit, and  
wherein the third variable resistance circuit is coupled to the first variable  
resistance circuit.
13. The apparatus of Claim 12,  
wherein the feedback circuit further includes a fourth variable resistance circuit,  
the fourth variable resistance circuit includes a replica of the second variable  
resistance circuit, and  
wherein the fourth variable resistance circuit is coupled to the fourth variable  
resistance circuit.
14. The apparatus of Claim 12, wherein  
the feedback circuit further includes:  
a transistor that is coupled between the third variable resistance circuit and  
the fourth variable resistance circuit;  
a first operational amplifier circuit that is coupled between the transistor  
and the third variable resistance circuit; and  
a second operational amplifier circuit that is coupled between the  
transistor and the fourth variable resistance circuit.
15. The apparatus of Claim 14,  
wherein the first operational amplifier circuit is configured to adjust a resistance  
that is associated with the first variable resistance circuit and a resistance that is  
associated with the third variable resistance circuit, and  
wherein the second operational amplifier circuit is configured to adjust a  
resistance that is associated with the second variable resistance circuit and a resistance  
that is associated with the fourth variable resistance circuit.

16. The apparatus of Claim 14,  
wherein the output driver circuit further includes a first current source circuit that is coupled to the first variable resistance circuit,  
the feedback circuit further includes:  
a replica resistor that is coupled in parallel with the transistor;  
a second current source circuit that is a replica of the first current source circuit; and  
a third operational amplifier circuit that is coupled to the first variable resistance circuit, the third variable resistance circuit, and the transistor, and  
wherein the third operational amplifier circuit is configured to adjust the transistor such that the first current source and the second current each provide an approximately constant current.
17. A differential driver circuit comprising:  
an output driver circuit, including:  
differential amplifier circuitry that is configured to provide a differential output signal in response to a differential input signal;  
a first variable resistance circuit that is configured to vary a resistance that is associated with the first variable resistance circuit in response to a first control signal; and  
a second variable resistance circuit that is configured to vary a resistance that is associated with the second variable resistance circuit in response to a second control signal; and  
a feedback circuit that is configured to provide the first control signal and the second control signal, wherein a source resistance of the output driver circuit appears to a load as substantially similar to a termination resistance of the load.
18. The differential driver circuit of Claim 17,  
wherein the output driver circuit is further configured to provide a monitor signal,  
the feedback circuit includes:

a third variable resistance circuit that is configured to vary a resistance that is associated with the third variable resistance circuit in response to the first control signal,

wherein the third variable resistance circuit is a replica of the first variable resistance circuit;

a fourth variable resistance circuit that is configured to vary a resistance that is associated with the fourth variable resistance circuit in response to the second control signal, wherein

the fourth variable resistance circuit is a replica of the second variable resistance circuit;

a transistor that is coupled between the third variable resistance circuit and the fourth variable resistance circuit;

a first operational amplifier that is configured to provide the first control signal;

a second operational amplifier that is configured to provide the second control signal; and

a third operational amplifier circuit that is coupled to the first variable resistance circuit, the third variable resistance circuit, and the transistor, wherein

the third operational amplifier circuit is configured to modulate the transistor in response to the monitor signal such that the first current source circuit and the second current source circuit each provide approximately constant current.

19. The differential driver circuit of Claim 18,  
wherein the output driver circuit further includes:

a first current source circuit that is coupled to the first variable resistance circuit and the feedback circuit; and

a first current sink circuit that is coupled to the second variable resistance circuit and the feedback circuit,

the feedback circuit further includes:

a second current source circuit that is a replica of the first current source circuit;

a second current sink circuit that is a replica of the first current sink circuit;

a fourth operational amplifier circuit that is configured to bias the first and second current source circuits in response to a first upper reference signal and a first feedback signal; and

a fifth operational amplifier circuit that is configured to bias the first and second current sink circuits in response to a first lower reference signal and a second feedback signal,

the transistor is coupled between a first feedback node and a second feedback node,

the first operational amplifier circuit is configured to provide the first control signal in response to a third feedback signal that is received at the first feedback node and a second upper reference signal, and

wherein the second operational amplifier circuit is configured to provide the second control signal in response to a fourth feedback signal that is received at the second feedback node and a second lower reference signal.

20. A differential driver circuit, comprising:

means for providing a differential output signal to a load having a termination resistance;

means for providing a source resistance; and

means for adjusting the source resistance to be substantially equivalent to a termination resistance.